



**HARDWOOD**

**GARDEN STATE TILE**

Together We Can Design For Life



The ceramic wood is suitable for different destinations of use, ensuring an ultra-natural effect.



# PERFECT

## PROJECT

FLOOR DESIGN

Relax Beige - 8"x40"

WALL DESIGN

Relax Beige - 8"x40"



The elegance of wood reveals its characteristic to adapt in any space, creating a synergy with other materials.

# FULL IMMERSION

**PROJECT**  
FLOOR DESIGN  
Happy Walnut - 8"x40"




# HARDWOOD

COLORED BODY PORCELAIN TILE

FEATURES AND BENEFITS



**FADING RESISTANT**  
stable chromatically over time



**DOESN'T BEND**  
hard and compact



**ECO-FRIENDLY AND SAFE**



**PET FRIENDLY**  
dog and cat nails proof



**RESISTANT TO FROST**  
snow and ice proof



**FLOOR HEAT FRIENDLY**



**RESISTANT TO ACID**



**EASY TO KEEP CLEAN**

**VOC FREE**  
NO VOC  
volatile organic compound



**WATER PROOF**  
doesn't absorb



**FIRE PROOF**  
doesn't burn or smoke

# HARDWOOD

SIZE 8"x40"

## COLORED BODY PORCELAIN TILE

### RELAX BEIGE



#### Available size



8"x40"  
± 0.35" / 9 mm

#### Color shading



V2

### HAPPY WALNUT



#### Available size



8"x40"  
± 0.35" / 9 mm

#### Color shading



V2

The colour of tiles printed in this catalogue may differ from actual tiles. Tile color reproductions in this catalogue are representative only. Slight tone and shade variations are inherent in porcelain tiles. Before selecting a colour, we recommend that you contact your local representative, who will provide you with a sample piece of the requested tile.

This porcelain tile product is manufactured with a V2 shade variation. Remember that the amount of colour as well as the texture of each piece may vary from tile to tile. Inspect the product immediately upon delivery and select tiles from many boxes during installation to minimize and blend any possible colour difference.

#### Color Shading




# HARDWOOD

## TRIM TILES

## INFORMATION

### COLORED BODY PORCELAIN TILE

	COVE BASE  6"x12"
RELAX BEIGE	•
HAPPY WALNUT	•

### RECOMMENDED USE

Recommended for indoor floors, walls, countertops, and outdoor walls in commercial and residential application. Not recommended for outdoor application or horizontal exterior surfaces. Recommended offset no greater than 30%. If a staggered pattern is required for tiles of 20" inches or longer.










### CARE AND MAINTENANCE

Do not apply any wax or sealer to the product after installation. Regular cleaning is the best way to keep tiles looking good. Use clean, hot water (add household cleaner for more aggressive cleaning). Rinse thoroughly and dry with a soft cloth to prevent water spots.

# HARDWOOD

## TILE PERFORMANCE DATA

### COLORED BODY PORCELAIN TILE

PHYSICAL PROPERTIES	TEST ASTM	NORTH AMERICAN STANDARD A137.1*	RESULTS
 Water absorption *	C373	≤ 0.5%	COMPLY WITH ANSI A137.1
 DCOF Average dynamic coefficient of friction **	BOT 3000 test	≥ 0.42	≥ 0.42
 Resistance to freeze/thaw cycling *	C1026	As reported	RESISTANT
 Warpage (edge)	C485	Warpage ± 0.4% or ± 0.05 in	COMPLY WITH ANSI A137.1
 Warpage (diagonal)	C485	Warpage ± 0.4% or ± 0.07 in	COMPLY WITH ANSI A137.1
 Wedging	C502	± 0.25% or ± 0.03 in	COMPLY WITH ANSI A137.1
 Chemical resistance	C650	As reported	UNAFFECTED
 Breaking strength	C648	250 lbf or greater	COMPLY WITH ANSI A137.1
 Thickness	C499	Range: 0.04 in	COMPLY WITH ANSI A137.1

\* Average values referred to our production and related to the matt finish of the product.

\*\* As far as values relating to the matt finish of the product and to tests carried out by certified external laboratories whose results are available upon request at Headoffice, we are willing to check the lot you are interested in purchasing.

- Be sure to use tiles belonging to the same caliber.
- Test results are available on request.
- Tiles can be slippery when wet. We recommend to make sure that the surface is always dry.
- The information provided can be subject to change.

