

1. PRODUCT NAME

Alfalux Hills Color: Any

2. MANUFACTURER Head Quarters Offices Alfalux Ceramiche Via Della Repubblica 16 Roteglia di Castellarano,

[taly

Ph.: +39.0536.869211 Fax:+39.0536.851502

3. PRODUCT DESCRIPTION

Hills is a full body porcelain replicating the movement of the Burlington stone, contemporary and technical, designed for paving large areas where cleaning is a key factor. Designed for great performances its technical test meet or exceed the most important ASTM tests.

4. THECNICAL DATA

Di : I	AOTAAT I	I	LAIC I
Physical	ASTM Test	Industry	Alfalux
Properties		Standards	Results
Matau Alaaanatia	0070	Lanca and acco	0.00
Water Absorption	C373	Impervious	<0.06
		< 0.5%	
DCOF Lappato	ANSI A137.1	>0.42	Meet or Exceed
DCOF	ANSI A137.1	>0.42	Meet or Exceed
Natural / Matte			
Freeze Thaw	C1028	no requirements	Alfalux
Cycling			shows no evidence of damage
			damaye
_	04040	475 0	A.C. I
Deep	C1243	<175 mm3	Alfalux
Abrasion			< 130mm3 exceeds
			standards
Lloydooo	lo di coto i	No requirements	Alfalini
Hardness	Industry	No requirements	Alfalux exceeds 8 on Mohs scale
Mohs scale	scale	or standards	for hardness
Warpage	C485	Warpage +/-	Alfalux
	0400	0.40% on any edge	<0.40% on any edge
Average		0.4070 on any cage	Co.4070 on any dage
Edges			
Warpage	C485	Warpage +/-	Alfalux
Average	0400	0.40% on any diagonal	<0.40% on any diagonal
		l and the second state of	l
Diagnol			
Wedging	C502	Wedging	Alfalux
Average	0002	+/- 0.25%	< 0,25% Wedging
/ Wordgo		17 0.2070	
Chemical	C650	No requirements	Alfalux
resistance		'	unaffected
Breaking	C648	250lbf or greater	Alfalux
Sterngth			> than 400lbf