
State of Grace

Porcelain Stone®



State of Grace

Porcelain Stone[®]

Uplifting design, timeless tile

A delicate, elegant, classic blend of Italian marbles never age. With unique and inspired graphics, Crossville's State of Grace porcelain tile offers beauty to behold for a lifetime. State of Grace captures the beloved veining of grays with delicate black and brown tones for an even more vibrant presentation than the classics. Chevron planks, pickets, multiple mosaics, chair rail, and trim pieces work in harmony to provide options - and grace everywhere in your designs.

- field tiles ranging from 3 x 6 to 24 x 48
- 4 x 24 single bullnose and 2 x 12 cove base trim
- 3 x 3 hexagon, 2 x 2 square and herringbone mesh mounted mosaics
- plank sizes upon request



Shower Walls: **GRC01** ▶ State of Grace, 12 x 12 UPS finish
Shower Floor: **GRC01** ▶ State of Grace, Herringbone Mosaics UPS finish
Shower Pan Ledge: **GRC01** ▶ State of Grace, 4 x 12 UPS finish (Get Planked)

Color Palette

Available Colors




GRC01 ▶ State of Grace (UPS finish)



GRC01 ▶ State of Grace Satin (SAT finish)


Specialty Tile Sizes, Trim and Mosaics



2.5 x 12 Chevron Left and Right



3x6 Picket



3 x 3 Hex Mosaics

UPS Finish
Mesh mounted on a
276mm x 296mm sheet



2 x 2 Mosaics

UPS Finish
Mesh mounted on a
298mm x 298mm sheet



Herringbone Mosaic

UPS Finish
Mesh mounted on
a 295mm x 341mm sheet
(Coverage area 0.8186 sf)

Get Planked!




Our Porcelain Stone® products are available in popular plank shapes with no minimum order and quick fulfillment. See website for more details and sizes.




* Globally Sourced

Specifications

Sizes



3 x 3 Hex Mosaics
UPS Finish
Mesh mounted on a
276mm x 296mm
sheet



2 x 2 Mosaics
UPS Finish
Mesh mounted on a
298mm x 298mm
sheet



Herringbone Mosaic
UPS Finish
Mesh mounted on a
295mm x 341mm sheet
(Coverage area 0.8186 sf)

Sizes & Finishes

Field Tile

Nominal (in)	Actual (mm)	Thickness (mm)	UPS Finish	Satin Finish
3 x 6	72 x 147	10.5	GRC01.10306UPS	GRC01.10306SAT
3 x 6 Picket	72 x 146	10.5	GRC01.136UPSPCK	GRC01.136SATPCK
6 x 24	147 x 597	10.5	GRC01.10624UPS	GRC01.10624SAT
2.5 x 12 Chevron Right	64 x 305	10.5	GRC01.10312UCVR	GRC01.10312SCVR
2.5 x 12 Chevron Left	64 x 305	10.5	GRC01.10312UCVL	GRC01.11312SCVL
12 x 12	297 x 297	10.5	GRC01.11212UPS	GRC01.11212SAT
12 x 24	297 x 597	10.5	GRC01.11224UPS	GRC01.11224SAT
24 x 24	597 x 597	10.5	GRC01.12424UPS	GRC01.12424SAT
24 x 48	597 x 1219	10.5	GRC01.12448UPS	GRC01.12448SAT

Actual measurements stated in inches indicate tile is calibrated (non-rectified).

Actual measurements stated in mm indicate tile is rectified. All field tile is rectified with a recommended 3mm grout joint.

Mosaics

Nominal (in)	Actual (mm)	Thickness (mm)	UPS Finish	Grout Joint (mm)
3 x 3 Hexagon	276 x 296	10.5	GRC01.13HEXUMOS	3.5
2 x 2 Square	298 x 298	10.5	GRC01.10202UMOS	3
Herringbone	295 x 341	10.5	GRC01.1HBUPSMOS	2.5

Coordinating Trim

Nominal (in)	Actual (mm)	Thickness (mm)	UPS Finish	Satin Finish
4 x 24 Single Bullnose	96 x 597	10.5	GRC01.10424BNS	GRC01.10424SABN
2 x 12 Cove Base	45 x 297	10	GRC01.10212CBS	-



4 x 24 Single Bullnose



2 x 12 Cove Base

* Globally Sourced

Product Performance



	UPS	Satin	
Breaking Strength	>500 lbf	>500 lbf	ASTM C648
Bond Strength	>200 psi	>200 psi	ASTM C482
Chemical Resistance	Class A	Class B	ASTM C650
Frost Resistance	Unaffected	Unaffected	ASTM C1026
Water Absorption	<0.20%	<0.20%	ASTM C373
Scratch Hardness	7	5	Mohs Scale

Wet Dynamic Coefficient of Friction Range

UPS	0.42 - 0.52	AcuTest sm
SAT	0.31 - 0.41	AcuTest sm

Shade & Texture Index

State of Grace has a shade variation of V2.



V1 Uniform appearance

V2 Slight Variation

V3 Moderate Variation

V4 Substantial Variation

This porcelain tile product is produced with a V2 variation. Expect that the amount of color and texture on each piece may vary slightly. Inspect the product upon delivery and for best results, blend tile from several cartons during installation.

State of Grace

Crossville, Inc.

PO Box 1168
Crossville, TN
38557

Phone 931.484.2110
Fax 931.456.2956
E-Mail Crossc@CrossvilleInc.com
Web CrossvilleInc.com

Recommended Use

State of Grace is recommended for interior floors, walls, countertops, and exterior walls in both residential and commercial applications. State of Grace is not recommended for exterior horizontal surfaces or exterior paving. **The satin finish is not recommended for wet areas where standing water may occur.** If offset pattern is required for tiles 15 inches or longer, Crossville® recommended an offset of not greater than 33%. See CrossvilleInc.com for detailed installation instructions.

Wet Area Use for State of Grace Mosaics

Crossville® produces the State Of Grace 3 x 3 hexagon and 2 x 2 mosaics with the Cross-Sheen® (UPS) finish. The AcuTestsm wet Dynamic COF of State of Grace is ≥ 0.42. Their small sizes ensure frequent grout joints which provides traction and drainage.

Crossville cannot control situations involving incorrect installation, improper slope to the drain for elimination of standing water and poor surface cleaning.

This information is provided so that customers may make a realistic and informed decision when comparing State of Grace to other tile products in wet area environments, such as residential/commercial bathrooms, showers, and interior pool decks.

Information listed here is subject to change. Please refer to CrossvilleInc.com for the latest, most accurate information.

Shower Walls: **GRC01** ▶ State of Grace, 12 x 12 UPS finish

Shower Floor: **GRC01** ▶ State of Grace, Herringbone Mosaic UPS finish

On the cover

GRC01 ▶ State of Grace, 24 x 48 UPS finish

Care and Maintenance

Regular cleaning is the best way to keep State Of Grace tile looking good for years to come. Use clean, hot water (combined with a household cleaner for more aggressive cleaning). Rinse thoroughly and dry with a soft cloth. No waxes are needed.

State Of Grace satin requires a grout release prior to grouting. More information regarding the care and maintenance of Crossville® products is available at CrossvilleInc.com.

Hydrotect

Our porcelain tiles are available with Hydrotect. Crossville's revolutionary invisible coating harnesses the power of light, water, and oxygen to create the best defense against dirt and pollution. Whether indoors or out, floors and walls stay cleaner, providing a superior experience in any space. For complete details check our website at CrossvilleInc.com.

 **HYDROTECT**[™]
by  **CROSSVILLE.**



Trade Organizations



Environmentally Aware



LIT-GRC-18