


## TECHNICAL INFORMATION & PLUS

### FORMATI - SIZES



RETTIFICATO

80 x 80  
32" x 32"



RETTIFICATO

60 x 120  
24" x 48"



RETTIFICATO | GRIP

60 x 60  
24" x 24"




RETTIFICATO

30 x 60  
12" x 24"




RETTIFICATO

7,4 x 30  
3" x 12"




MOSAICO

30 x 30  
12" x 12"



HEXAGON


25 x 34  
10" x 13"



PLANK


30 x 60  
12" x 24"

### PEZZI SPECIALI - SPECIAL ITEMS




GRADONE COSTA RETTA  
RETTIFICATO | GRIP

30 x 60 x 4  
12" x 24" x 12/3"



GRADONE ANGOLARE COSTA RETTA  
RETTIFICATO | GRIP

30 x 30 x 4  
12" x 12" x 12/3"



GRADINO  
RETTIFICATO | GRIP


30 x 60  
12" x 24"

GRADONE COSTA RETTA  
RETTIFICATO

60 x 120 x 4  
24" x 48" x 12/3"

GRADONE ANGOLARE COSTA RETTA  
RETTIFICATO

60 x 120 x 4  
24" x 48" x 12/3"



ELEMENTO A L  
RETTIFICATO | GRIP

30 x 60 x 5  
12" x 24" x 2"



BATTISCOPA SMALTATO  
RETTIFICATO

7 x 60  
3" x 24"

9,5 x 80  
4" x 32"



### TECHNICAL FEATURES

	standards	characteristics or properties	declared values
	ISO 10545-3	water absorption	<0.5%
	ISO 10545-4	breaking strength	35 N/mm <sup>2</sup>
	ISO 10545-13	resistance to acid	GLA
	ISO 10545-12	frost resistance	resiste frost proof
	ISO 10545-14	stain resistance	4
	ISO 10545-2	surface flatness	±0.5%
		thickness	10 mm
	DIN51097 DIN51130 DCOF BOT 3000	static coefficient of friction	A R10 > 0.42
	DIN51097 DIN51130 DCOF BOT 3000	static coefficient of friction	A+B+C R11 > 0.42
		color shade variations	V3 variazione moderata V3 moderate variation

### PACKING

mm	inch		spessore thickness	pezzi/sc pcs/box	mq/sc sqm/box	kg/sc kgs/box	sc/pl box/pal	mq/pl sqm/pal	kg/pl kgs/pal
60x120	24"x48"	rettificato	10	2	1.44	32.51	30	43.20	975.30
60x60	24"x24"	rettificato   grip	10	3	1.08	23.92	40	43.20	956.80
30x60	12"x24"	rettificato	10	6	1.08	23.76	40	43.20	950.40
80x80	32"x32"	rettificato	10	2	1.28	28.50	40	51.20	1140.00
7.4x30	3"x12"	rettificato	10	40	0.89	19.50	60	53.28	1170.00
30x30	12"x12"	mosaico	11	0.99	20.00	36	35.64	720.00	
30x60	12"x24"	plank		5		19.65			
25x34	10"x13"	hexagon		6		11.10			
7x60	3"x24"	battiscopa smaltato rettificato		12		11.16			
9.5x80	4"x32"	battiscopa smaltato rettificato		8		14.24			
30x60	12"x24"	gradino rettificato   grip		8		31.60			
30x60x4	12"x24"x 23/4"	gradone costa retta rettificato   grip		4		19.40			
60x120x4	24"x48"x 23/4"	gradone costa retta rettificato		2		34.80			
30x30x4	12"x12"x 23/4"	gradone angolare costa retta   grip		2		4.40			
60x120x4	24"x48"x 23/4"	gradone angolare costa retta		1		18.20			
30x60x5	12"x24"x 2"	elemento a L   grip		4		17.20			

the indicated weight includes the supporting pallet -

### JOINT

for rectified material, we recommend a minimum of 2 mm of grout when using one size of piece only and 3 mm for multi-size laying solutions