

## 2CM PEDESTAL WAIVER

Garden State Tile recommends the use of Bison Paver Trays on all 2CM Porcelain Paver Materials, when pedestal heights are above .75" – 36." **Should the installer choose not to use Bison Innovative Products 2CM Tray System, GST will not be liable for any damages or injury incurred by breakage or wind lift. The purchaser and installer assume all liability.**

Bison Paver Trays: Ideal for use with Bison Pedestals, the Bison Paver Tray offers a thin and lightweight paver backing to enhance the impact resistance of pavers when used in pedestal applications. Bison Paver Trays meet testing for non-combustible surface material, are made of weather resistant galvanized metal, and are recommended for use on Bison Pedestals over 0.75" and up to 36" in height. See Product Information for dimension and weight options. Note: Confirm your paver sizes in metric units prior to purchasing Paver Trays.

WARNING: OUTDOOR PAVINGS INSTALLED UNGLUED ABOVE THE GROUND LEVEL ARE SUBJECT TO THE ACTION OF THE WIND, WITH THE RISK, IN SOME CASES, OF BECOMING AIRBORNE. THE MANUFACTURER RECOMMENDS THE ASSISTANCE OF A QUALIFIED PROFESSIONAL IN ORDER TO CHECK THE SUITABILITY OF THE INSTALLATION SYSTEM ABOVE THE GROUND ADOPTED, IN ACCORDANCE WITH THE LOCAL LAWS AND REGULATIONS AND THE CONDITIONS OF USE. FAILURE TO DO SO COULD RESULT IN SERIOUS INJURY OR PROPERTY DAMAGE.

A CERAMIC SLAB INSTALLED ON A RAISED PEDESTAL SYSTEM MAY FRACTURE ON IMPACT IF A HEAVY OBJECT IS DROPPED ONTO IT FROM A HEIGHT, WITH A RISK OF INJURY TO ANYONE STANDING OR WALKING ON SUCH SLAB. FAILURE TO ADHERE TO THE MANUFACTURER'S INSTRUCTIONS FOR INSTALLATION OF SLABS ON RAISED PEDESTAL SYSTEMS MAY RESULT IN SERIOUS INJURY. FOR FURTHER INFORMATION AND RECOMMENDATIONS CONCERNING THE INSTALLATION SYSTEMS PLEASE REFER TO <https://gstile.com/product/bison-paver-2cm-tray-24-x-24/>

NOTE: IF THE APPLICATION OF THE 20 MM (¾") SLABS FORESEES THE CERAMIC PRODUCT USED IN STRUCTURAL INSTALLATIONS, THE PROJECT ENGINEER AND/OR CUSTOMER MUST CAREFULLY ASSESS THE PROJECT REQUIREMENTS WITH REGARD TO THE TECHNICAL SPECIFICATIONS OF THE SLABS. TO PREVENT THE RISK OF DAMAGE OR INJURY, THE MANUFACTURER RECOMMENDS: WITH REGARD TO A RAISED FLOOR INSTALLATION A CERAMIC SLAB MAY FRACTURE ON IMPACT IF A HEAVY OBJECT FALLS ON IT FROM ANY SIGNIFICANT HEIGHT. THEREFORE, THE MANUFACTURER RECOMMENDS CHECKING THE SPECIFIC INTENDED USE BEFORE STARTING THE INSTALLATION.

INSTALLATION PROVIDED BELOW:

IN CERTAIN CONDITIONS, REINFORCING MESH OR TRAY MUST BE APPLIED ON THE BACK OF THE SLABS (MESH PLUS OR GALVANIZED STEEL SHEET) SUPPLIED AND APPLIED BY THE MANUFACTURER; WITH REFERENCE TO ANY DRY INSTALLATION SYSTEM OF FLOORING ABOVE THE GROUND LEVEL, THE MANUFACTURER RECOMMENDS TO COMPLY WITH LOCAL REGULATIONS AND CONDITIONS OF USE WITH REGARD TO WIND-LOAD, LOADBEARING, SEISMIC EVENTS, ETC. FAILURE TO COMPLY WITH THESE RECOMMENDATIONS MAY LEAD TO IMPROPER USE OF THE PRODUCT AND COULD CAUSE SERIOUS DAMAGE OR INJURY.

Purchaser must sign and date in agreement of this policy and information:

\_\_\_\_\_  
SIGNATURE

\_\_\_\_\_  
DATE