# Classic Grooves Porcelain Stone®



# Classic Grooves Porcelain Stone®

### Feel the visual rhythm of Classic Grooves from Crossville.

Graphic movement is enhanced with subtle striations and tone-ontone optics. The swirling surface glints and glows with a soft, sophisticated sheen. The end result is a series of graphicallyenhanced warm and cool neutral tiles complemented by an array of decorative accents. Sustainably made in the USA\*, Classic Grooves is at once timeless as it is contemporary.

Classic Grooves comes in two unpolished field tile sizes: 12"x24" and 24"x24". Mosaic options emulate palm designs, with two linear accents featuring metallic glazes, a sheet mosaic of individually cut palm shapes, and a traditional 2x2 mosaic. All tile is rectified for a clean, crisp installation that's smooth to the touch yet provides the slip resistance a commercial space requires.

Perfect for your playlist, this Classic Grooves will never lose its beat.

- Color-coordinating collection for versatility
- Cross-Sheen® for easy cleaning
- Field tile rectified
- A wide variety of accents and mosaics
- Recommended grout joint: 3mm

\*field tile manufactured in Crossville, TN.





CGR01 ► Forty-Five 24 x 24

Shower Floor: CGR02 > B-Side 2 x 2 Mosaic Vanity: PC001 > Baltic UP Crossville Porcelain Slabs Wall: CGR02 > B-Side 12 x 24 Floor: CGR02 > B-Side 12 x 24

Deco not available

# Color Palette

### Available Colors







CGR03 ► Liner Notes UPS



CGR04 ▶ Turntable UPS



CGR05 ► Sleeve UPS



### **Available Mosaics**



**CGR01** ► Forty-Five UPS 2 x 2 Square Mosaic



**CGR03** ► Liner Notes UPS 2 x 2 Square Mosaic



CGR05 ► Sleeve UPS 2 x 2 Square Mosaic



**CGR01** ► Forty-Five UPS Palm Mosaic



CGR03 ► Liner Notes UPS Palm Mosaic



CGR05 ► Sleeve UPS Palm Mosaic



**CGR02** B-Side UPS 2 x 2 Square Mosaic



**CGR04** Turntable UPS 2 x 2 Square Mosaic



CGR02 ► B-Side UPS Palm Mosaic



**CGR04** ► Turntable UPS Palm Mosaic

# Specifications

#### Sizes Shown in CGR04 Turntable







2 x 2 Palm Square Mosaic UPS<sup>†</sup> Mosaic UPS

<sup>†</sup> Due to this mosaic's design, caution should be used when installing on surfaces that might contact bare skin or other delicate materials. To prevent possible injury or damage from sharp corners that might be exposed above the grout line, install per ANSI 108 guidelines in order to minimize or prevent lippage.

#### Get Planked!

Our Porcelain Stone® products are available in popular plank shapes with no minimum order and quick fulfilment.

See website for more details and sizes.



#### Sizes & Finishes

fied	Available in all co	lors	
Actual (mm)	Thickness (mm)	Grout Joint (mm)	Finish
297 x 597	9.5	3	UPS
597 x 597	9.5	3	UPS
	297 x 597	Actual (mm) Thickness (mm) 297 x 597 9.5	Actual (mm)Thickness (mm)Grout Joint (mm)297 x 5979.53

Note: All field tile is rectified with a 3mm grout joint.

Mosaic	Available in all colors			
Nominal (in)	Sheet (mm)	Thickness (mm)	Grout Joint (mm)	Finish
2 x 2 Square Mosaics*	298 x 298	9.5	3	UPS
Palm Mosaic**†	370 x 345	9.5	2	UPS

\* Mounted on 12 x 12 sheet with 3mm grout joints \*\* Mounted on 15 x 14 sheet with 2mm grout joints

<sup>†</sup> Due to this mosaic's design, caution should be used when installing on surfaces that might contact bare skin or other delicate materials. To prevent possible injury or damage from sharp corners that might be exposed above the grout line, install per ANSI 108 guidelines in order to minimize or prevent lippage.

Coordinating Trim				
Nominal (in)	Actual (mm)	Thickness (mm)	Grout Joint (mm)	Finish
4 x 24 Single Bullnose	96 x 597	9.5	3	UPS
6 x 12 Cove Base	150 x 297	9.5	3	UPS
		• • • • • • • • • • • • • • • • • • • •		

4 x 24 Single Bullnose

6 x 12 Cove Base


Product Performance		
Breaking Strength	≥450 lbf	ASTM C648
Bond Strength	>200 psi	ASTM C482
Chemical Resistance	Unaffected	ASTM C650
Frost Resistance	Resistant	ASTM C1026
Water Absorption	<0.50%	ASTM C373
Scratch Hardness	7	Mohs Scale

Net Dynamic Coefficient of Friction Range
---

UPS	0.42 - 0.52

#### Shade & Texture Index

Classic Grooves has a shade variation of V2



V1 Uniform appearance V2 Slight Variation

ANSI A326.3

V2 Modorato Variati

4 Substantial Variation

This porcelain tile product is produced with a V2 variation. Expect that the amount of color and texture on each piece may vary slightly. Inspect the product upon delivery and for best results, blend tile from several cartons during installation.

#### **Recommended Use**

Classic Grooves is recommended for interior floors, walls, countertops, and exterior walls in both residential and commercial applications. Classic Grooves is not recommended for exterior horizontal surfaces or exterior paving. **If offset pattern is required for tiles 15 inches or longer, Crossville\* recommended an offset of not greater than 33%.** See CrossvilleInc.com for detailed installation instructions.

#### Wet area use for Classic Grooves Mosaics

Crossville<sup>®</sup> produces the Classic Grooves 2 x 2 and Palm mosaics with the Cross-Sheen<sup>®</sup> (UPS) finish. The ANSI A326.3 wet Dynamic COF of Classic Grooves is  $\geq$ 0.42. Their small sizes ensure frequent grout joints which provides traction and drainage. Crossville cannot control situations involving incorrect installation, improper slope to the drain for elimination of standing water and poor surface cleaning.

This information is provided so that customers may make a realistic and informed decision when comparing Classic Grooves to other tile products in wet area environments, such as residential/commercial bathrooms, showers, and interior pool decks.

#### **Care and Maintenance**

Regular cleaning is the best way to keep Classic Grooves tile looking good for years to come. Use clean, hot water (combined with a household cleaner for more aggressive cleaning). Rinse thoroughly and dry with a soft cloth. No waxes are needed. More information regarding the care and maintenance of Crossville<sup>®</sup> products is available at CrossvilleInc.com.

#### Our Warranty

Crossville Inc. guarantees that its products will meet or exceed the performance specifications outlined in ANSI A137.1- 2012 and in the performance data section of the Crossville, Inc. general product catalog. For complete details check our website at CrossvilleInc.com.

#### HydroTect™

Our porcelain tiles are available with Hydrotect<sup>™</sup>. Crossville's revolutionary invisible coating harnesses the power of light, water, and oxygen to create the best defense against dirt and pollution. Whether indoors or out, floors and walls stay cleaner, providing a superior experience in any space. For complete details check our website at CrossvilleInc.com.

#### 🕸 HYDROTECT 🖱

by 🔶 CROSSVILLE,

#### Crossville<sup>®</sup> Sample Express

Visit the website to learn more: CrossvilleInc.com/Products/ Classic-Grooves

Loose Samples for Architects & Designers

#### Loose Tile Samples

Sizes may vary depending on product series Max. of 4 large field tile per order

Standard Shipping FedEx Ground

#### CrossvilleInc.com

If you want a better idea of what Crossville tile would look like in a particular room setting, simply visit our website and click on Cross-Vision. This powerful software tool allows you to visualize different types of Crossville tile. In addition, you'll find comprehensive information about Crossville's entire portfolio of products. You can also learn about the latest styles and trends from industry experts, download detailed care and maintenance instructions for our various products, or browse electronic versions of Crossville's product brochures. So whether you need information about Crossville products or tile in general, please visit us at CrossvilleInc.com. Information listed here is subject to change.

Information listed here is subject to change. Please refer to CrossvilleInc.com for the latest, most accurate information.




Floor: **CGR04** > Turntable 24 x 24 Bar Front: **CGR04** > Turntable Palm Mosaic Countertop - **PC010** Night Watch Crossville Porcelain Slabs









WSGBC MEMBER







## Classic Grooves

Crossville, Inc.

PO Box 1168 Crossville, TN 38557 Phone931.484.2110Fax931.456.2956E-MailCrossc@CrossvilleInc.comWebCrossvilleInc.com

